



PEK SERIES UVC LAMP AND BALLAST KIT

MODEL	(A) OVERALL LAMP LENGTH	VOLTAGE	AMP DRAW	* UVC OUTPUT	WEIGHT	REPLACEMENT LAMP	REPLACEMENT BALLAST	BALLAST DIMS. (H x W x L)
PEK-18-120	16.00" / 406mm	120 VAC	0.25	128 uW/cm ²	3.0 lbs.	GCL-18	TXG270	1.00" x 1.72" x 8.50"
PEK-18-230	16.00" / 406mm	208-230 VAC	0.15	128 uW/cm ²	3.0 lbs.	GCL-18	TXG275	1.00" x 1.72" x 9.50"
PEK-18-277	16.00" / 406mm	277 VAC	0.10	128 uW/cm ²	3.0 lbs.	GCL-18	TXG280	1.00" x 1.72" x 9.50"
PEK-24-120	22.00" / 559mm	120 VAC	0.60	198 uW/cm ²	3.0 lbs.	GCL-24	TXG270	1.00" x 1.72" x 8.50"
PEK-24-230	22.00" / 559mm	208-230 VAC	0.35	198 uW/cm ²	3.0 lbs.	GCL-24	TXG275	1.00" x 1.72" x 9.50"
PEK-24-277	22.00" / 559mm	277 VAC	0.30	198 uW/cm ²	3.0 lbs.	GCL-24	TXG280	1.00" x 1.72" x 9.50"
PEK-36-120	34.00" / 864mm	120 VAC	0.80	339 uW/cm ²	3.1 lbs.	GCL-36	TXG270	1.00" x 1.72" x 8.50"
PEK-36-230	34.00" / 864mm	208-230 VAC	0.40	339 uW/cm ²	3.1 lbs.	GCL-36	TXG275	1.00" x 1.72" x 9.50"
PEK-36-277	34.00" / 864mm	277 VAC	0.35	339 uW/cm ²	3.1 lbs.	GCL-36	TXG280	1.00" x 1.72" x 9.50"
PEK-48-120	46.00" / 1168mm	120 VAC	1.15	479 uW/cm ²	3.2 lbs.	GCL-48	TXG270	1.00" x 1.72" x 8.50"
PEK-48-230	46.00" / 1168mm	208-230 VAC	0.60	479 uW/cm ²	3.2 lbs.	GCL-48	TXG275	1.00" x 1.72" x 9.50"
PEK-48-277	46.00" / 1168mm	277 VAC	0.50	479 uW/cm ²	3.2 lbs.	GCL-48	TXG280	1.00" x 1.72" x 9.50"
PEK-60-120	58.00" / 1473mm	120 VAC	1.50	620 uW/cm ²	3.3 lbs.	GCL-60	TXG285	1.00" x 1.72" x 19.25"
PEK-60-230	58.00" / 1473mm	208-230 VAC	0.80	620 uW/cm ²	3.3 lbs.	GCL-60	TXG290	1.00" x 1.72" x 19.25"
PEK-60-277	58.00" / 1473mm	277 VAC	0.70	620 uW/cm ²	3.3 lbs.	GCL-60	TXG295	1.00" x 1.72" x 19.25"

* @ 1 METER IN 45 DEGREE F. - 400 FPM AIRFLOW

