

Model No.: **AC-1000R**

**Specification:**

Type :	Ceiling Flush Mounted Mode (Air input from central side Air frame & output from two side)
Voltage / wattage :	AC110V / 220V 60Hz / 120W
Air flow :	HI : 1050CFM MED : 850CFM LOW : 510CFM
Motor temperature :	HI : 42.1°C MED : 39.9°C LOW : 42.2°C Auto Cut Motor Protector 125°C
Speed control :	Wireless controller-4stages OFF / HI / MED / LOW (timer shutdown 1.2.4.8. Hr)
Noise ratings(db) :	HI : 52db MED : 47db LOW : 42db (extra sleeping design)
Dimensions surface size / At ceiling :	Outlook appearance: 1200mm × 620mm × 1mm Building in: 1170mm × 580mm × 345mm
Indicator light :	Stage operate / high wattage indicator
Turbine motor / Fan pleated :	2 Set High function, low noise, strong wind, large suction, two layers turbine fan.
Air input / output design :	Diagonal input, single side output, 360° solid circulation far wind high efficiency
Cell voltage(two-stage) :	Ionizing Section : 8,000VDC Collecting Section : 4,000VDC
Collecting boxes / pitch :	71pcs. / 4mm
Quantity of electronic cell :	2 Set
Collect efficiency :	0.3μm—7μm 98.6% Certification by Industrial Technology Research Innovation Taiwan. NO 5F55RD1D00-070
Weight :	43KG
Suitable square meter :	Within 130 square meters (depending on pollution situation)
Accessory with machine :	Wireless control, Active carbon, filter technology brochure.