

Model No.:**AC-P601R**

Specification:

Type :	Floor type air cleaner
Voltage / wattage :	AC110V / 220V 50Hz / 61W
Air flow :	HI : 450CFM MED : 345CFM LOW : 185CFM
Motor temperature :	HI : 51.5°C MED : 44.8°C LOW : 43.4°C Auto Cut Motor Protector 125°C
Speed control :	Wireless controller-4stages OFF / HI / MED / LOW (timer shutdown 1.2.4.8.Hr)
Noise ratings(db) :	HI : 52db MED : 47db LOW : 36db(extra sleeping design)
Dimensions surface size / At ceiling :	Outlook appearance:940mm × 487mm × 330mm
Indicator light :	Stage operate / high wattage indicator
Turbine motor / Fan pleated :	1 Set High function ,low noise ,strong wind, large suction, two layers turbine fan.
Air input / output design :	Air supply from central of machine, and sent out the clean air from top, direct wind moving, / independent plate on top , 360 degree 3D circulate, far wind blow, high efficiency.
Cell voltage(two-stage) :	Ionizing Section : 8,000VDC Collecting Section : 4,000VDC
Colleting boxes / pitch :	71pcs. / 4mm
Quantity of electronic cell :	1 Set
Collect efficiency :	0.3μm—7μm 96% Certification by Industrial Technology Research Innovation Taiwan. NO 5F55RD1D00-070
Weight :	29 KG
Suitable square meter :	Within 55 square meter (depending on pollution situation)
Accessory with machine :	Wireless control, Active carbon, filter technology brochure.