

FX SERIES

Compact oil mist collectors

1250 m³/hr – 2750 m³/hr



The industry-proven solution for eliminating oil mist from manufacturing environments, [trusted by world leading manufacturers since 1969](#)

Compact | Quiet | Efficient

Multiple Mounting Options

FX oil mist collectors are available with a number of mounting options including floor stands, machine mounts and the mobile CSX unit.

Worldwide Compatibility

Filtermist oil mist collector units are used in more than 60 countries worldwide and are designed to operate efficiently on a wide range of industrial power supplies.

Stainless Steel

Filtermist FX and S series oil mist collectors are available in standard mild steel construction and also stainless-steel versions for use in hazardous or corrosive environments.



Tech Data

Model	Airflow m ³ /hr	Motor ¹		A	B	C	D	Weight kg	Noise ² dBA
				mm	mm	mm	mm		
FX4002	1250 @ 50Hz 1500 @ 60Hz	1.1kW 50Hz 200v, 220v, 380v, 400v, 415v	1.1kW 60Hz 200v, 220v, 230v, 440v, 460v, 480v	357	540	35	148	309	398
FX5002	1675 @ 50Hz 2000 @ 60Hz	1.5kW 50Hz 200v, 220v, 380v, 400v, 415v	1.5kW 60Hz 200v, 220v, 230v, 440v, 460v, 480v	357	639	35	198	378	398
FX6002	2000 @ 60Hz 2400 @ 60Hz	2.2kW 50Hz 200v, 220v, 380v, 400v, 415v	2.2kW 60Hz 220v, 230v, 440v, 460v, 480v	438	643	35	198	432	485

- ¹Motors to be used on specified voltages only.
- ²Results are in test conditions ± 3% tolerance. Local variations and in use conditions may affect readings.

