

SERIES

Ultra-compact oil mist collector

180 m³/hr – 950 m³/hr



The industry-proven solution for eliminating oil mist from manufacturing environments, [trusted by world leading manufacturers since 1969](#)

Compact | Quiet | Efficient

Multiple Mounting Options

Filtermist's S Series oil mist collectors are compact, lightweight and designed to be directly mounted onto machine tools. They can also be fitted using floor stands and machine mounting brackets.

Energy Efficient Oil Mist Extraction

Fitted with either 0.18kW or 0.55kW motors, S Series oil mist collector units are low energy users.

Stainless Steel

Filtermist FX and S series oil mist collectors are available in standard mild steel construction and also stainless-steel versions for use in hazardous or corrosive environments.



Tech Data

Model	Airflow m ³ /hr	Motor ¹		A	B	C	D	Weight kg	Noise ² dBA
				mm	mm	mm	mm		
S200	180 @ 50Hz	0.18kW 50Hz 200v, 220v, 380v, 400v, 415v	0.18kW 60Hz 200v, 220v, 230v, 440v, 460v, 480v	260	302	30	73	9	62
	215 @ 60Hz								
S400	425 @ 50Hz	0.55kW 50Hz 200v, 220v, 380v, 400v, 415v	0.55kW 60Hz 200v, 220v, 230v, 440v, 460v, 480v	325	401	35	148	14	65
	500 @ 60Hz								
S800	800 @ 60Hz	0.55kW 50Hz 200v, 220v, 380v, 400v, 415v	0.55kW 60Hz 220v, 230v, 440v, 460v, 480v	325	453	35	148	15	67
	950 @ 60Hz								

- ¹Motors to be used on specified voltages only.
- ²Results are in test conditions \pm 3% tolerance. Local variations and in use conditions may affect readings.

