

## Coarse Efficiency / Pre-Filtration

### Media Rolls & Pads

#### Material Overview

- ◆ Low initial resistance
- ◆ High dust holding capacity
- ◆ For Pre-Filtration of Air Inlet

#### Application

- ◆ For fine filtration in air conditioning devices and installations, particularly final filtration in automotive spray booths and drying cabinets



### Standard

ASHRAE 52.2:2017	MERV 4 - 8
EN779:2012	G1 - G4
Media Type	Polyester Fibre By Roll
Rec. Final Resistance	250 Pa
Max Operating Temperature	80°C

### Product Details

Model	Dimension W x L (M)	Thickness (mm)	Initial P.D (mmAq)	Final P.D (mmAq)	Face Velocity (m/sec)
<b>G1 Classification Efficiency AFI &lt; 65%</b>					
CG	1 x 50	3	3	15	2.5
<b>G2 Classification (MERV 4) Efficiency AFI 75% - 80%</b>					
CG	1 x 50	5	4	15	2.5
<b>G3 Classification (MERV 6) Efficiency AFI 85% - 90%</b>					
CG	1 x 20	10	5	20	2.5
	1 x 20	15	6	20	2.5
<b>G4 Classification (MERV 8) Efficiency NBS 30%-35%</b>					
CG	1 x 20	20	7	20	2
	1 x 20	25	7	20	2
	1 x 20	30	8	20	2

\* Other dimensions are available on request \*

## TOBERO PTE LTD

25 KAKI BUKIT ROAD 4, #07-49/50 SYNERGY  
SINGAPORE 417800  
TEL: 6749 0933 FAX: 6741 9550