

Terminal Filter Housing

Fan Filter Unit – DC Type

Material Overview

- ◆ 3D Airfoil turbo fan High-efficient & Low-noise
- ◆ Flexible change design
- ◆ Convenient design of installation
- ◆ Easy carry/handle friendly design
- ◆ Multiple safe protect devices



Standard

Housing Material	Galvanized, Stainless Steel, Aluminum
Power Supply	220V 1 Phase
Air Velocity	0.3-0.5 m/s
Total Static Pressure	TSP 250 Pa
Cabinet Material	Stainless (SUS430, SUS304), AL-ZN Alloy Sheet, Galvanized Sheet Iron
Fan Runner	Airfoil Turbo Fan Runner
Airflow Control	Stepless Speed Monitored Type with RS485
Filter Efficiency	Over 99.99% at particle Dia., Over 0.3µm or 99.9999% at 0.1µm
Filter Frame	Aluminum
Voltage Type	1 ph 220V-240V
Noise Level (dBA)	< 60
Optional	Pre-Filter, Collar, Insulation, Hanger, Electrical Cable

Product Details

Model	Housing Size mm (H x W x D)	Filter Size mm (H x W x D)	Rated Airflow (CMM)	Power Consumption (W)
FFU-220EC	575 x 575 x 320	570 x 570 x 70	10	90
FFU-240EC	575 x 1175 x 280	570 x 1170 x 70	15	90
FFU-440EC	1175 x 1175 x 330	1170 x 1170 x 70	30	120

* Other dimensions are available on request *

TOBERO PTE LTD

25 KAKI BUKIT ROAD 4, #07-49/50 SYNERGY
SINGAPORE 417800
TEL: 6749 0933 FAX: 6741 9550